

Safety Data Sheet

according to 2001/58/EC

UV adhesive "Lamifix" B678-0

Print date : 24.08.2005

Product code : BO5209360

Page 1 of 5

1. Identification of the substance/preparation and of the company/undertaking**1.1 Identification of the substance or preparation**

UV adhesive "Lamifix" B678-0

Use of the substance/preparation
adhesives**1.2 Company/undertaking identification**

Company name : BOHLE AG
 Street : Dieselstr. 10
 Place : D-42781 Haan
 Contact person : Uwe Adler
 e-mail : uadler@bohle.de
 Inquiry office : Produktmanagement

Telephone : 02129 5568-0
 Telefax : 02129 5568 282

2. Composition/information on ingredients

Chemical characterization (preparation)
 Methacrylate/Acrylate resin(s).

Hazardous components

EC-No.	CAS-No.	Chemical name	Quantity	Classification
212-782-2	868-77-9	2-hydroxyethyl methacrylate	20-35 %	Xi R36/38-43
	688-84-6	2-Ethylhexylmethacrylate	20-35 %	Xi R36/37/38

Full text of each relevant R phrase can be found in heading 16.

3. Hazards identification**Classification**

Symbols : Irritant
 R-phrases :
 May cause sensitization by skin contact.
 Irritating to eyes, respiratory system and skin.

4. First aid measures**After inhalation**

Move to fresh air. Consult a physician after significant exposure.

After contact with skin

Wash off with soap and plenty of water. If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

5. Fire-fighting measures**Suitable extinguishing media**water spray dry powder foam carbon dioxide (CO₂)

Safety Data Sheet

according to 2001/58/EC

UV adhesive "Lamifix" B678-0

Print date : 24.08.2005

Product code : BO5209360

Page 2 of 5

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Special exposure hazards arriving from substance or preparation itself, combustion products, resulting gases

@N05.00218100 Carbon monoxide, nitrogen oxides (NOx)

Special protective equipment for fire-fighters

Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions

Use personal protective equipment.

Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

Methods for cleaning up/taking up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

7. Handling and storage

7.1 Handling

Advice on safe handling

Harmful: danger of serious damage to health by prolonged exposure through inhalation and in contact with skin. Ensure adequate ventilation, especially in confined areas. Breathing apparatus needed only when aerosol or mist is formed. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

Advice on protection against fire and explosion

No special technical protective measures required.

7.2 Storage

Requirements for storage rooms and vessels

Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

No special restrictions on storage with other products.

Further information on storage conditions

Keep away from direct sunlight. Keep away from heat.

8. Exposure controls/personal protection

8.1 Exposure limit values

8.2 Exposure controls

Occupational exposure controls

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

Protective and hygiene measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. When using, do not eat, drink or smoke. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

Safety Data Sheet

according to 2001/58/EC

UV adhesive "Lamifix" B678-0

Print date : 24.08.2005

Product code : BO5209360

Page 3 of 5

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment.

Hand protection

rubber gloves

Eye protection

tightly fitting safety goggles

Skin protection

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use.

9. Physical and chemical properties

9.1 General information

Physical state : liquid
 Colour : clear
 Odour : characteristic

9.2 Important health, safety and environmental information

Test method

Changes in the physical state

Flash point :	89 °C
Density (at 20 °C) :	1,03 g/cm ³
Water solubility :	insoluble
Viscosity / dynamic : at (20 °C)	600 mPa·s

Solvent content

0%

10. Stability and reactivity

Conditions to avoid

Stable under recommended storage conditions.

Materials to avoid

oxidizing agents, amines, strong acids

Hazardous decomposition products

No decomposition if used as directed.

11. Toxicological information

Irritancy and corrosiveness

Skin irritation. Severe eye irritation.

Sensitising effect

May cause sensitisation by skin contact.

Subacute, subchronic and prolonged toxicity

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.

12. Ecological information

Ecotoxicity

Ecological injuries are not known or expected under normal use.

13. Disposal considerations

Safety Data Sheet

according to 2001/58/EC

UV adhesive "Lamifix" B678-0

Print date : 24.08.2005

Product code : BO5209360

Page 4 of 5

Waste disposal number of waste from residues/unused products :

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

14. Transport information

Land transport (ADR/RID)Inland waterways transportMarine transportAir transportFuther Information

Not a dangerous substance as defined in the above regulations.

15. Regulatory information

15.1 Labelling

Indication of danger : Xi - Irritant



Xi - Irritant

Hazardous component(s) to be indicated on label

2-hydroxyethyl methacrylate

R phrases :

43 May cause sensitization by skin contact.
36/37/38 Irritating to eyes, respiratory system and skin.

S phrases :

03 Keep in a cool place.
15 Keep away from heat.
21 When using do not smoke.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
35 This material and its container must be disposed of in a safe way.
37 Wear suitable gloves.
41 In case of fire and/or explosion do not breathe fumes.
52 Not recommended for interior use on large surface areas.
24/25 Avoid contact with skin and eyes.

15.2 National regulations

16. Other information

List of relevant R phrases

43 May cause sensitization by skin contact.
36/38 Irritating to eyes and skin.
36/37/38 Irritating to eyes, respiratory system and skin.

Other data

Safety Data Sheet

according to 2001/58/EC

UV adhesive "Lamifix" B678-0

Print date : 24.08.2005

Product code : BO5209360

Page 5 of 5

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)