

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Acecut 5929 Cutting fluid

Print date: 25.01.2017

Product code: BO5002837

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Acecut 5929 Cutting fluid

Further trade names

BO 5002807S, Sample
BO 5002830, 5 l
BO 5002807, 30 l
BO 5002837, 200 l
BO 5002843, 1000 l

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

cutting fluid

1.3. Details of the supplier of the safety data sheet

Company name: BOHLE AG
Street: Dieselstr. 10
Place: D-42781 Haan
Telephone: +49 2129 5568-0
e-mail: info@bohle.de
Contact person: Klaus Nehren
e-mail: MSDS@bohle.de
Internet: www.bohle-group.com
Responsible Department: Chemie

Telefax: +49 2129 5568-282

Telephone: +49 2129 5568-276

1.4. Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
Aspiration hazard: Asp. Tox. 1
Hazard Statements:
May be fatal if swallowed and enters airways.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics

Signal word: Danger**Pictograms:****Hazard statements**

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Acecut 5929 Cutting fluid

Print date: 25.01.2017

Product code: BO5002837

Page 2 of 7

P308+P311 water/shower.
IF exposed or concerned: Call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Petroleum distillates

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
	Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics			80-100%
	926-141-6		01-2119456620-43	
	Asp. Tox. 1; H304			
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether			<10%
	225-878-4	603-052-00-8	01-2119475527-28	
	Skin Irrit. 2; Eye Irrit. 2; H315 H319			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

First aider: Pay attention to self-protection!
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
If symptoms persist, call a physician.

After contact with skin

Wash off with soap and plenty of water.
If symptoms persist, call a physician.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids. Remove contact lenses, if present and easy to do. Continue rinsing.
Consult a physician.

After ingestion

Rinse mouth thoroughly with water.
Do NOT induce vomiting.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.
Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Acecut 5929 Cutting fluid

Print date: 25.01.2017

Product code: BO5002837

Page 3 of 7

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂)
Extinguishing powder
alcohol resistant foam
Water spray jet

Unsuitable extinguishing media

high volume water jet

5.2. Special hazards arising from the substance or mixture

Heating or fire can release toxic gas.
Carbon dioxide, Carbon monoxide

5.3. Advice for firefighters

Standard procedure for chemical fires.
Self-contained respirator (breathing apparatus) (DIN EN 133)

Additional information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.
Do not allow to enter into soil/subsoil.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Provide adequate ventilation.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Dispose of waste according to applicable legislation.

6.4. Reference to other sections

Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.
To avoid risks to man and the environment, comply with the instructions for use.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Usual measures for fire prevention.
Take precautionary measures against static discharges.
Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.
Store in a place accessible by authorized persons only.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Acecut 5929 Cutting fluid

Print date: 25.01.2017

Product code: BO5002837

Page 4 of 7

Protect against direct sunlight.

Advice on storage compatibility

Do not store together with oxidizing agents

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

cutting fluid

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether			
Worker DNEL, long-term		dermal	systemic	44 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	270,5 mg/m ³

PNEC values

CAS No	Substance	Value
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether	
Freshwater		0,525 mg/l
Marine water		0,0525 mg/l
Freshwater sediment		2,36 mg/kg
Marine sediment		0,236 mg/kg
Soil		0,16 mg/kg

8.2. Exposure controls
Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Do not breathe vapours or spray mist.

Avoid contact with skin, eyes and clothing. Take off all contaminated clothing immediately.

Wash hands before breaks and immediately after handling the product.

When using do not eat or drink. Do not smoke.

Keep away from food, drink and animal feedingstuffs.

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber), NBR (Nitrile rubber)

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

DIN EN 13034 (Type 6 limited splash-tight)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Acecut 5929 Cutting fluid

Print date: 25.01.2017

Product code: BO5002837

Page 5 of 7

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Combination filtering device (EN 14387)
Respirator with filter for organic vapour, Recommended Filter type: A-P2

Environmental exposure controls

Do not flush into surface water or sanitary sewer system.
Do not allow to enter into soil/subsoil.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: like: Hydrocarbons

Test method

pH-Value: not applicable

Changes in the physical state

Melting point: < -20 °C
Initial boiling point and boiling range: >190 °C
Flash point: 71 °C ISO 2719
Lower explosion limits: 0,6 vol. %
Upper explosion limits: 7 vol. %
Ignition temperature: >270 °C DIN 51794
Auto-ignition temperature not auto-flammable
Vapour pressure: <1 hPa
(at 20 °C)
Density (at 20 °C): 0,79 g/cm³ DIN 51757
Water solubility: insoluble
Viscosity / dynamic: 3 mPa·s DIN 54453
(at 20 °C)
Viscosity / kinematic: <2 mm²/s
(at 40 °C)

9.2. Other information

Vapours can form explosive mixtures with air.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Protect against direct sunlight.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Acecut 5929 Cutting fluid

Print date: 25.01.2017

Product code: BO5002837

Page 6 of 7

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
	Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics			
	oral	LD50 >5000 mg/kg	Rat	OECD 401
	dermal	LD50 >5000 mg/kg	Rabbit	OECD 402
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether			
	oral	LD50 >2000 mg/kg	Rat	OECD 423
	dermal	LD50 >2000 mg/kg	Rat	OECD 402

Irritation and corrosivity

May cause eye irritation with susceptible persons.

Aspiration hazard

May be harmful if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

This product has no known eco-toxicological effects.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether				
	Acute fish toxicity	LC50 >100 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna (Big water flea)	

12.3. Bioaccumulative potential

Bioaccumulation is unlikely.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

slightly water endangering

Do not flush into surface water or sanitary sewer system.

Avoid subsoil penetration.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Acecut 5929 Cutting fluid

Print date: 25.01.2017

Product code: BO5002837

Page 7 of 7

Advice on disposal

Can be incinerated, when in compliance with local regulations.

Contaminated packaging

Dispose of completely emptied containers as combustible waste or metal waste depending on the material.

SECTION 14: Transport information

Other applicable information

Not dangerous goods in the meaning of ADR/RID, ADNR, IMDG-Code, ICAO/IATA-DGR

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)