

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Glass edge laquer

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Clear coating

**1.3. Details of the supplier of the safety data sheet**

|                         |                     |                              |
|-------------------------|---------------------|------------------------------|
| Company name:           | BOHLE AG            |                              |
| Street:                 | Dieselstr. 10       |                              |
| Place:                  | D-42781 Haan        |                              |
| Telephone:              | +49 2129 5568-0     | Telefax: +49 2129 5568-282   |
| e-mail:                 | info@bohle.de       |                              |
| Contact person:         | Klaus Nehren        | Telephone: +49 2129 5568-276 |
| e-mail:                 | MSDS@bohle.de       |                              |
| Internet:               | www.bohle-group.com |                              |
| Responsible Department: | Chemie              |                              |

**1.4. Emergency telephone number:** Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Harmful to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

isopropyl acetate

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

2-methylpropan-1-ol; iso-butanol

butan-1-ol; n-butanol

**Signal word:** Danger**Pictograms:**

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 2 of 12

**Hazard statements**

- |      |  |
|------|--|
| H225 | Highly flammable liquid and vapour.                |
| H318 | Causes serious eye damage.                         |
| H336 | May cause drowsiness or dizziness.                 |
| H412 | Harmful to aquatic life with long lasting effects. |

**Precautionary statements**

- |                |  |
|----------------|--|
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P243           | Take precautionary measures against static discharge.  |
| P271           | Use only outdoors or in a well-ventilated area.  |
| P273           | Avoid release to the environment.  |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310           | Immediately call a POISON CENTER/doctor.   |
| P370+P378      | In case of fire: Use Carbon dioxide (CO <sub>2</sub> ), Sand, Extinguishing powder to extinguish.                                |

**Special labelling of certain mixtures**

- |        |   |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
|--------|---|

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

One-pack performance coatings

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 3 of 12

**Hazardous components**

| CAS No     | Chemical name  |              |                  | Quantity |
|------------|--|--------------|------------------|----------|
|            | EC No  | Index No     | REACH No         |          |
|            | Classification according to Regulation (EC) No. 1272/2008 [CLP]  |              |                  |          |
| 64-17-5    | ethanol, ethyl alcohol   |              |                  | <50 %    |
|            | 200-578-6  | 603-002-00-5 | 01-2119457610-43 |          |
|            | Flam. Liq. 2, Eye Irrit. 2; H225 H319  |              |                  |          |
| 108-21-4   | isopropyl acetate  |              |                  | <25 %    |
|            | 203-561-1  | 607-024-00-6 | 01-2119537214-46 |          |
|            | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066   |              |                  |          |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha                        |              |                  | <25 %    |
|            | 265-151-9  |              | 01-2119473851-33 |          |
|            | Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411                               |              |                  |          |
| 67-63-0    | propan-2-ol; isopropyl alcohol; isopropanol  |              |                  | <10 %    |
|            | 200-661-7  | 603-117-00-0 | 01-2119457558-25 |          |
|            | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336  |              |                  |          |
| 123-86-4   | n-butyl acetate  |              |                  | <10 %    |
|            | 204-658-1  | 607-025-00-1 | 01-2119485493-29 |          |
|            | Flam. Liq. 3, STOT SE 3; H226 H336 EUH066  |              |                  |          |
| 78-83-1    | 2-methylpropan-1-ol; iso-butanol   |              |                  | <10 %    |
|            | 201-148-0  | 603-108-00-1 | 01-2119484609-23 |          |
|            | Flam. Liq. 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H315 H318 H335 H336                    |              |                  |          |
| 71-36-3    | butan-1-ol; n-butanol  |              |                  | <2,5 %   |
|            | 200-751-6  | 603-004-00-6 | 01-2119484630-38 |          |
|            | Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336 |              |                  |          |
| 107-98-2   | 1-methoxy-2-propanol; monopropylene glycol methyl ether  |              |                  | <2,5 %   |
|            | 203-539-1  | 603-064-00-3 | 01-2119457435-35 |          |
|            | Flam. Liq. 3, STOT SE 3; H226 H336   |              |                  |          |

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

Take off immediately all contaminated clothing.

**After inhalation**

Move to fresh air. Consult a physician after significant exposure. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. Call a physician immediately.

**After contact with skin**

Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

**After contact with eyes**

 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists, consult a specialist.

**After ingestion**

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Give sodium sulfate as

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 4 of 12

laxative (1 tablespoon in 1 glass of water) with plenty of activated coal.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media**

high volume water jet

**5.2. Special hazards arising from the substance or mixture**

In use may form flammable/explosive vapour-air mixture.

Fire may cause evolution of: Carbon monoxide, Carbon dioxide )

**5.3. Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

**Additional information**

Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation.

Keep away from heat and sources of ignition.

Avoid contact with skin and eyes. Do not breathe vapour.

**6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Local authorities should be advised if significant spillages cannot be contained.

**6.3. Methods and material for containment and cleaning up**

Provide adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Collect in closed and suitable containers for disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation as well as local exhaust at critical locations.

Provide room air exhaust at ground level.

Avoid formation of aerosol. Do not breathe vapour/aerosol.

Avoid contact with the skin and the eyes.

**Advice on protection against fire and explosion**

Take precautionary measures against static discharges. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 5 of 12

smoke.

**7.2. Conditions for safe storage, including any incompatibilities**
**Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.

**SECTION 8: Exposure controls/personal protection**
**8.1. Control parameters**
**Exposure limits (EH40)**

| CAS No   | Substance            | ppm  | mg/m <sup>3</sup> | fibres/ml | Category      | Origin |
|----------|----------------------|------|-------------------|-----------|---------------|--------|
| 107-98-2 | 1-Methoxypropan-2-ol | 100  | 375               |           | TWA (8 h)     | WEL    |
|          |                      | 150  | 560               |           | STEL (15 min) | WEL    |
| 78-83-1  | 2-Methylpropan-1-ol  | 50   | 154               |           | TWA (8 h)     | WEL    |
|          |                      | 75   | 231               |           | STEL (15 min) | WEL    |
| 71-36-3  | Butan-1-ol           | -    | -                 |           | TWA (8 h)     | WEL    |
|          |                      | 50   | 154               |           | STEL (15 min) | WEL    |
| 123-86-4 | Butyl acetate        | 150  | 724               |           | TWA (8 h)     | WEL    |
|          |                      | 200  | 966               |           | STEL (15 min) | WEL    |
| 64-17-5  | Ethanol              | 1000 | 1920              |           | TWA (8 h)     | WEL    |
|          |                      | -    | -                 |           | STEL (15 min) | WEL    |
| 108-21-4 | Isopropyl acetate    | -    | -                 |           | TWA (8 h)     | WEL    |
|          |                      | 200  | 849               |           | STEL (15 min) | WEL    |
| 67-63-0  | Propan-2-ol          | 400  | 999               |           | TWA (8 h)     | WEL    |
|          |                      | 500  | 1250              |           | STEL (15 min) | WEL    |

**DNEL/DMEL values**

| CAS No                   | Substance                                   | Exposure route | Effect   | Value                 |
|--------------------------|---|----------------|----------|-----------------------|
| 67-63-0                  | propan-2-ol; isopropyl alcohol; isopropanol |                |          |                       |
| Consumer DNEL, long-term |   | oral           | systemic | 26 mg/kg bw/day       |
| Consumer DNEL, long-term |   | dermal         | systemic | 319 mg/kg bw/day      |
| Worker DNEL, long-term   |   | dermal         | systemic | 888 mg/kg bw/day      |
| Consumer DNEL, long-term |   | inhalation     | systemic | 89 mg/m <sup>3</sup>  |
| Worker DNEL, long-term   |   | inhalation     | systemic | 500 mg/m <sup>3</sup> |

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 6 of 12

**PNEC values**

| CAS No  | Substance  |            |
|---------|--|------------|
|         | Environmental compartment                        | Value      |
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol      |            |
|         | Freshwater                                       | 140,9 mg/l |
|         | Freshwater (intermittent releases)               | 140,9 mg/l |
|         | Marine water                                     | 140,9 mg/l |
|         | Freshwater sediment                              | 552 mg/kg  |
|         | Marine sediment                                  | 552 mg/kg  |
|         | Micro-organisms in sewage treatment plants (STP) | 2251 mg/l  |
|         | Soil   | 28 mg/kg   |

**8.2. Exposure controls**

**Appropriate engineering controls**

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

**Protective and hygiene measures**

Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Take off all contaminated clothing immediately. Keep away from food, drink and animal feedingstuffs. When using do not eat or drink. Do not smoke. Wash hands before breaks and at the end of workday.

**Eye/face protection**

safety glasses with side-shields conforming to EN166

**Hand protection**

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber)  $\geq 0,5\text{mm}$ , NBR (Nitrile rubber)  $\geq 0,35\text{mm}$

Breakthrough time (maximum wearing time)  $\geq 480\text{ min}$ .

**Skin protection**

impervious clothing

**Respiratory protection**

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state: liquid  
 Colour: clear  
 Odour: characteristic

**Test method**

pH-Value (at 20 °C): not applicable

**Changes in the physical state**

Melting point: not determined

Initial boiling point and boiling range: 78 °C

Flash point: 2 °C DIN 51755

**Explosive properties**

In use, may form flammable/explosive vapour-air mixture.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 7 of 12

|  |                         |
|--|-------------------------|
| Lower explosion limits:  | 0,8 vol. %              |
| Upper explosion limits:  | 19 vol. %               |
| Ignition temperature:  | 200 °C                  |
| <b>Auto-ignition temperature</b>   | not auto-flammable      |
| Vapour pressure:<br>(at 50 °C)   | 1.100 hPa               |
| Density (at 20 °C):  | 0,870 g/cm <sup>3</sup> |
| Water solubility:  | insoluble               |
| <b>Solubility in other solvents</b><br>miscible with most organic solvents |                         |
| Viscosity / dynamic:<br>(at 20 °C)   | not determined          |
| Flow time:<br>(at 20 °C)   | 13 s                    |
| Solvent separation test:   | <3%                     |
| Solvent content:   | ca. 79%                 |
| <b>9.2. Other information</b>  |                         |
| Solid content:   | 21%                     |

**SECTION 10: Stability and reactivity****10.1. Reactivity**

None under normal processing.

**10.2. Chemical stability**

No decomposition if used as directed.

**10.3. Possibility of hazardous reactions**

Vapours may form explosive mixture with air.

**10.4. Conditions to avoid**Keep away from heat and sources of ignition.  
Take action to prevent static discharges.**10.5. Incompatible materials**

strong acids and oxidizing agents

**10.6. Hazardous decomposition products**

None known.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

LD50/oral/rat = &gt;2000mg/kg

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 8 of 12

| CAS No   | Chemical name   |                       |         |        |        |
|----------|---|-----------------------|---------|--------|--------|
|          | Exposure route  | Dose                  | Species | Source | Method |
| 64-17-5  | ethanol, ethyl alcohol                                  |                       |         |        |        |
|          | oral  | LD50<br>mg/kg 6200    | Rat     | IUCLID |        |
|          | inhalative (4 h) vapour                                 | LC50 95,6 mg/l        | Rat     | RTECS  |        |
| 108-21-4 | isopropyl acetate                                       |                       |         |        |        |
|          | oral  | LD50<br>mg/kg 6750    | Rat     | GESTIS |        |
|          | dermal  | LD50<br>mg/kg > 17400 | Rabbit  | GESTIS |        |
|          | inhalative (4 h) vapour                                 | LC50 50,6 mg/l        | Rat     |        |        |
| 67-63-0  | propan-2-ol; isopropyl alcohol; isopropanol             |                       |         |        |        |
|          | oral  | LD50<br>mg/kg 4570    | Rat     |        |        |
|          | dermal  | LD50<br>mg/kg 13400   | Rabbit  |        |        |
|          | inhalative (4 h) vapour                                 | LC50 30 mg/l          | Rat     |        |        |
| 78-83-1  | 2-methylpropan-1-ol; iso-butanol                        |                       |         |        |        |
|          | oral  | LD50<br>mg/kg > 2830  | Rat     |        |        |
|          | dermal  | LD50<br>mg/kg > 2000  | Rat     |        |        |
|          | inhalative (4 h) vapour                                 | LC50 > 24 mg/l        | Rat     |        |        |
| 71-36-3  | butan-1-ol; n-butanol                                   |                       |         |        |        |
|          | oral  | ATE<br>mg/kg 500      |         |        |        |
| 107-98-2 | 1-methoxy-2-propanol; monopropylene glycol methyl ether |                       |         |        |        |
|          | oral  | LD50<br>mg/kg > 5000  | Rat     | IUCLID |        |
|          | dermal  | LD50<br>mg/kg 11000   | Rabbit  |        |        |

**Practical experience**
**Other observations**

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**SECTION 12: Ecological information**
**12.1. Toxicity**

Ecological injuries are not known or expected under normal use.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Glass edge laquer

Revision date: 04.10.2017

Product code: BO5007005

Page 9 of 12

| CAS No   | Chemical name   |                        |           |                                      |        |        |
|----------|---|------------------------|-----------|--------------------------------------|--------|--------|
|          | Aquatic toxicity  | Dose                   | [h]   [d] | Species                              | Source | Method |
| 64-17-5  | ethanol, ethyl alcohol                                  |                        |           |                                      |        |        |
|          | Acute crustacea toxicity                                | EC50 9268 - 14221 mg/l | 48 h      | Daphnia magna                        | IUCLID |        |
| 67-63-0  | propan-2-ol; isopropyl alcohol; isopropanol             |                        |           |                                      |        |        |
|          | Acute fish toxicity                                     | LC50 9640 mg/l         | 96 h      | Pimephales promelas (fathead minnow) |        |        |
|          | Acute algae toxicity                                    | ErC50 >2000 mg/l       | 72 h      | Desmodesmus subspicatus              |        |        |
| 78-83-1  | 2-methylpropan-1-ol; iso-butanol                        |                        |           |                                      |        |        |
|          | Acute fish toxicity                                     | LC50 1430 mg/l         | 96 h      | Pimephales promelas                  |        |        |
|          | Acute algae toxicity                                    | ErC50 1250 mg/l        |           | Desmodesmus subspicatus              |        |        |
|          | Acute crustacea toxicity                                | EC50 1439 mg/l         | 48 h      | Daphnia magna                        |        |        |
| 107-98-2 | 1-methoxy-2-propanol; monopropylene glycol methyl ether |                        |           |                                      |        |        |
|          | Acute fish toxicity                                     | LC50 4600 - 10000 mg/l | 96 h      | Leuciscus idus                       | IUCLID |        |
|          | Acute algae toxicity                                    | ErC50 > 1000 mg/l      | 72 h      | Selenastrum capricornutum            |        |        |
|          | Acute crustacea toxicity                                | EC50 > 500 mg/l        | 48 h      | Daphnia magna                        | IUCLID |        |

#### 12.2. Persistence and degradability

Readily biodegradable, according to appropriate OECD test.

#### 12.3. Bioaccumulative potential

##### Partition coefficient n-octanol/water

| CAS No   | Chemical name   | Log Pow |
|----------|---|---------|
| 64-17-5  | ethanol, ethyl alcohol                                  | -0,31   |
| 108-21-4 | isopropyl acetate                                       | 1,02    |
| 67-63-0  | propan-2-ol; isopropyl alcohol; isopropanol             | -0,16   |
| 78-83-1  | 2-methylpropan-1-ol; iso-butanol                        | 0,79    |
| 107-98-2 | 1-methoxy-2-propanol; monopropylene glycol methyl ether | -0,437  |

#### 12.4. Mobility in soil

The product evaporates readily.

##### Further information

hazardous to water (WGK 2)

Do not let product enter drains.

## SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

In accordance with local and national regulations.

##### Waste disposal number of waste from residues/unused products

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 10 of 12

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances  
Classified as hazardous waste.

**Waste disposal number of used product**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances  
Classified as hazardous waste.

**Waste disposal number of contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances  
Classified as hazardous waste.

**Contaminated packaging**

Non-contaminated packages may be recycled.  
Contaminated packages must be completely emptied and can be re-used following proper cleaning.  
Cleaning agent: n-butyl acetate

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Special Provisions: 601  
Limited quantity: 1 L  
Excepted quantity: E2  
Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 11 of 12

Special Provisions: 601  
 Limited quantity: 1 L  
 Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: -  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: A180  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y341  
 Excepted quantity: E2  
 IATA-packing instructions - Passenger: 353  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 364  
 IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

none

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not relevant

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3: ethanol, ethyl alcohol; isopropyl acetate; 2-methylpropan-1-ol; iso-butanol; 1-methoxy-2-propanol; monopropylene glycol methyl ether

Entry 29: Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Glass edge laquer**

Revision date: 04.10.2017

Product code: BO5007005

Page 12 of 12

2004/42/EC (VOC): 79%  
Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - water contaminating

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

|        |   |
|--------|---|
| H225   | Highly flammable liquid and vapour.                   |
| H226   | Flammable liquid and vapour.                          |
| H302   | Harmful if swallowed.                                 |
| H304   | May be fatal if swallowed and enters airways.         |
| H315   | Causes skin irritation.                               |
| H318   | Causes serious eye damage.                            |
| H319   | Causes serious eye irritation.                        |
| H335   | May cause respiratory irritation.                     |
| H336   | May cause drowsiness or dizziness.                    |
| H411   | Toxic to aquatic life with long lasting effects.      |
| H412   | Harmful to aquatic life with long lasting effects.    |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

**Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*