

according to Regulation (EC) No 1907/2006

UV adhesive VERIFIX B 690-0

Revision date: 07.06.2017

Product code: BO5209370

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

UV adhesive VERIFIX B 690-0

Further trade names

BO 5209370, 85 g

BO 5209372, 1000 g / BO 5209372S, Spacer, 1000 g

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

adhesives

1.3. Details of the supplier of the safety data sheet

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Klaus Nehren	Telephone: +49 2129 5568-276
e-mail:	MSDS@bohle.de	
Internet:	www.bohle-group.com	
Responsible Department:	Chemie	

1.4. Emergency telephone number: Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

May cause respiratory irritation.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

2-ethylhexyl methacrylate

2-hydroxyethyl methacrylate

Methyl methacrylate

Signal word: Warning**Pictograms:****Hazard statements**

H335

May cause respiratory irritation.

according to Regulation (EC) No 1907/2006

UV adhesive VERIFIX B 690-0

Revision date: 07.06.2017

Product code: BO5209370

Page 2 of 7

H319 Causes serious eye irritation.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Methacrylate/Acrylate resin(s).

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
688-84-6	2-ethylhexyl methacrylate			<30%
	211-708-6		01-2119490166-35	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 3; H315 H319 H317 H335 H412			
868-77-9	2-hydroxyethyl methacrylate			<30%
	212-782-2	607-124-00-X	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			
80-62-6	Methyl methacrylate			<1%
	201-297-1	607-035-00-6	01-2119452498-28	
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

First aider: Pay attention to self-protection!
 Get medical advice/attention if you feel unwell.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Irritation to respiratory tract

according to Regulation (EC) No 1907/2006

UV adhesive VERIFIX B 690-0

Revision date: 07.06.2017

Product code: BO5209370

Page 3 of 7

Skin contact : May cause an allergic skin reaction.

Eye contact : Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Extinguishing powder, Foam, Carbon dioxide (CO₂)

Unsuitable extinguishing media

High power water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide, nitrogen oxides (NO_x)

5.3. Advice for firefighters

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment (refer to section 8).

Provide adequate ventilation.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Avoid contact with skin and eyes.

Do not eat, drink or smoke when using this product.

Ensure adequate ventilation.

Advice on protection against fire and explosion

No special technical protective measures required.

Further information on handling

Avoid: UV-radiation/sunlight

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up.

Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

7.3. Specific end use(s)

according to Regulation (EC) No 1907/2006

UV adhesive VERIFIX B 690-0

Revision date: 07.06.2017

Product code: BO5209370

Page 4 of 7

adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapour. To follow: Occupational exposure limit values

Protective and hygiene measures

Wash hands before breaks and after work. When using do not eat, drink or smoke.
Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.
Recommended material: NBR (Nitrile rubber), VITON
Unsuitable material: Natural fibres (e.g. cotton)

Skin protection

Wear suitable protective clothing.

Respiratory protection

Usually no personal respiratory protection necessary. When using do not eat, drink or smoke.
In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (DIN EN 136/140)
Respirator with filter for organic vapour. Recommended Filter type: A (P2)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: characteristic

Test method

Changes in the physical state

Flash point: >100 °C
Density (at 20 °C): 1,1 g/cm³
Water solubility: insoluble
Viscosity / dynamic: 600 mPa·s
(at 23 °C)
Solvent content: 0%

SECTION 10: Stability and reactivity

according to Regulation (EC) No 1907/2006

UV adhesive VERIFIX B 690-0

Revision date: 07.06.2017

Product code: BO5209370

Page 5 of 7

10.1. Reactivity

Light / UV-radiation/sunlight
Oxidising agent, strong

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep cool. Protect from sunlight. Heat, flames and sparks.
In case of light influence: Polymerisation

10.5. Incompatible materials

Reducing agent, strong. Oxidising agent, strong
strong acids and strong bases

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.
Thermal decomposition can lead to the escape of irritating gases and vapours. Carbon monoxide (CO),
Carbon dioxide (CO₂), Hydrocarbons

SECTION 11: Toxicological information
11.1. Information on toxicological effects
Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
688-84-6	2-ethylhexyl methacrylate					
	oral	LD50 mg/kg	16465	Rat		
868-77-9	2-hydroxyethyl methacrylate					
	oral	LD50 mg/kg	5564	Rat		
	dermal	LD50 mg/kg	>5000	Rabbit		

SECTION 12: Ecological information
12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas	

12.2. Persistence and degradability

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
688-84-6	2-ethylhexyl methacrylate				
	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	88%	28		
	Readily biodegradable (according to OECD criteria).				

according to Regulation (EC) No 1907/2006

UV adhesive VERIFIX B 690-0

Revision date: 07.06.2017

Product code: BO5209370

Page 6 of 7

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
868-77-9	2-hydroxyethyl methacrylate	0,47

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Consult the appropriate local waste disposal expert about waste disposal.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances
Classified as hazardous waste.

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances
Classified as hazardous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenil work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV adhesive VERIFIX B 690-0

Revision date: 07.06.2017

Product code: BO5209370

Page 7 of 7

H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)