

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**UV adhesive VERIFIX B 690-0**

Revision date: 04.05.2022

Product code: BO5209370

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**
**1.1. Product identifier**

UV adhesive VERIFIX B 690-0

**Further trade names**

BO 5209370, 85 g

BO 5209372, 1000 g / BO 5209372S, Spacer, 1000 g

**1.2. Relevant identified uses of the substance or mixture and uses advised against**
**Use of the substance/mixture**

adhesives

**1.3. Details of the supplier of the safety data sheet**

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Dr. Martin Schade	Telephone: +49 2129 5568-300
e-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

**1.4. Emergency telephone number:**

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

**SECTION 2: Hazards identification**
**2.1. Classification of the substance or mixture**
**Regulation (EC) No 1272/2008**

Skin Irrit. 2; H315  
 Eye Irrit. 2; H319  
 Skin Sens. 1; H317  
 STOT SE 3; H335  
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**
**Regulation (EC) No 1272/2008**
**Hazard components for labelling**

2-ethylhexyl methacrylate  
 2-hydroxyethyl methacrylate  
 Methyl methacrylate

**Signal word:** Warning

**Pictograms:**

**Hazard statements**

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**UV adhesive VERIFIX B 690-0**

Revision date: 04.05.2022

Product code: BO5209370

Page 2 of 8

**Precautionary statements**

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Chemical characterization**

Methacrylate/Acrylate resin(s).

**Hazardous components**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
688-84-6	2-ethylhexyl methacrylate	<30 %
	211-708-6	
	01-2119490166-35	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 3; H315 H319 H317 H335 H412	
868-77-9	2-hydroxyethyl methacrylate	<30 %
	212-782-2	
	607-124-00-X	
	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317	
80-62-6	Methyl methacrylate	<1 %
	201-297-1	
	607-035-00-6	
	01-2119452498-28	
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335	

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
688-84-6	211-708-6	2-ethylhexyl methacrylate	<30 %
		oral: LD50 = 16465 mg/kg STOT SE 3; H335: >= 10 - 100	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	<30 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = 5050 mg/kg	
80-62-6	201-297-1	Methyl methacrylate	<1 %
		inhalation: LC50 = 78 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = 7900 mg/kg	

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

First aider: Pay attention to self-protection!  
Get medical advice/attention if you feel unwell.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

**After contact with skin**

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**UV adhesive VERIFIX B 690-0**

Revision date: 04.05.2022

Product code: BO5209370

Page 3 of 8

**After contact with eyes**

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

**After ingestion**

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Inhalation: Irritation to respiratory tract

Skin contact : May cause an allergic skin reaction.

Eye contact : Causes serious eye damage.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Extinguishing powder, Foam, Carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Carbon monoxide, nitrogen oxides (NO<sub>x</sub>)

**5.3. Advice for firefighters**

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

In the event of fire, wear self-contained breathing apparatus.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Wear personal protection equipment (refer to section 8).

Provide adequate ventilation.

**6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

Local authorities should be advised if significant spillages cannot be contained.

**6.3. Methods and material for containment and cleaning up****Other information**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

**6.4. Reference to other sections**

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Avoid contact with skin and eyes.

Do not eat, drink or smoke when using this product.

Ensure adequate ventilation.

**Advice on protection against fire and explosion**

No special technical protective measures required.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**UV adhesive VERIFIX B 690-0**

Revision date: 04.05.2022

Product code: BO5209370

Page 4 of 8

**Advice on general occupational hygiene**

Wash hands before breaks and after work. When using do not eat, drink or smoke.  
Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

**Further information on handling**

Avoid: UV-radiation/sunlight

**7.2. Conditions for safe storage, including any incompatibilities**
**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place.  
Keep container tightly closed. Keep locked up.  
Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

**SECTION 8: Exposure controls/personal protection**
**8.1. Control parameters**
**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	

**8.2. Exposure controls**
**Appropriate engineering controls**

Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapour. To follow: Occupational exposure limit values

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

safety glasses with side-shields conforming to EN166

**Hand protection**

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Recommended material: NBR (Nitrile rubber), VITON

Unsuitable material: Natural fibres (e.g. cotton)

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

Usually no personal respiratory protection necessary. When using do not eat, drink or smoke.  
In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (EN 136/140)  
Respirator with filter for organic vapour. Recommended Filter type: A (P2)

**SECTION 9: Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

Physical state: Liquid  
Colour: colourless  
Odour: characteristic

**Test method**
**Changes in the physical state**

Flash point: >100 °C  
pH-Value (at 21 °C): 4 5% emulsion

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**UV adhesive VERIFIX B 690-0**

Revision date: 04.05.2022

Product code: BO5209370

Page 5 of 8

Viscosity / dynamic: (at 23 °C)	600 mPa·s
Water solubility:	insoluble
Density (at 20 °C):	1,1 g/cm <sup>3</sup>

**9.2. Other information**

Solvent content: 0%

**Further Information****SECTION 10: Stability and reactivity****10.1. Reactivity**

Light / UV-radiation/sunlight  
Oxidising agent, strong

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Keep cool. Protect from sunlight. Heat, flames and sparks.  
In case of light influence: Polymerisation

**10.5. Incompatible materials**

Reducing agent, strong. Oxidising agent, strong  
strong acids and strong bases

**10.6. Hazardous decomposition products**

No decomposition if stored and applied as directed.  
Thermal decomposition can lead to the escape of irritating gases and vapours. Carbon monoxide (CO),  
Carbon dioxide (CO<sub>2</sub>), Hydrocarbons

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**UV adhesive VERIFIX B 690-0**

Revision date: 04.05.2022

Product code: BO5209370

Page 6 of 8

**Acute toxicity**

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
688-84-6	2-ethylhexyl methacrylate					
	oral	LD50 mg/kg	16465	Rat		
868-77-9	2-hydroxyethyl methacrylate					
	oral	LD50 mg/kg	5050	Rat		
	dermal	LD50 mg/kg	>5000	Rabbit		
80-62-6	Methyl methacrylate					
	oral	LD50 mg/kg	7900	Rat		
	dermal	LD50 mg/kg	>5000	Rabbit	OECD 402	
	inhalation (4 h) vapour	LC50	78 mg/l	Rat		

**SECTION 12: Ecological information**
**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas	
80-62-6	Methyl methacrylate					
	Acute fish toxicity	LC50	283 mg/l	96 h	Lepomis macrochirus (Bluegill)	
	Acute algae toxicity	ErC50	110 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50	69 mg/l	48 h	Daphnia magna (Big water flea)	

**12.2. Persistence and degradability**

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
688-84-6	2-ethylhexyl methacrylate				
	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	88%	28		
	Readily biodegradable (according to OECD criteria).				
80-62-6	Methyl methacrylate				
	aerob	94%	14		
	Readily biodegradable (according to OECD criteria).				

**12.3. Bioaccumulative potential**
**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
868-77-9	2-hydroxyethyl methacrylate	0,47
80-62-6	Methyl methacrylate	1,38

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**UV adhesive VERIFIX B 690-0**

Revision date: 04.05.2022

Product code: BO5209370

Page 7 of 8

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Disposal recommendations**

Consult the appropriate local waste disposal expert about waste disposal.

**List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - used product**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information**
**SECTION 15: Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2004/42/EC (VOC): 0 %  
0 g/l

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**
**Changes**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**UV adhesive VERIFIX B 690-0**

Revision date: 04.05.2022

Product code: BO5209370

Page 8 of 8

This data sheet contains changes from the previous version in section(s): 2.

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*