

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 02.09.2019

Product code: BO5209499

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Pyrosil Primer

Further trade names

BO 5209494, 50 ml, BO 5209490 SET, BO 5209491 SET
BO 5209498, 250 ml
BO 5209499, 1000 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

adhesives and/or sealants

1.3. Details of the supplier of the safety data sheet

| | | |
|-------------------------|-----------------|------------------------------|
| Company name: | BOHLE AG | |
| Street: | Dieselstr. 10 | |
| Place: | D-42781 Haan | |
| Telephone: | +49 2129 5568-0 | Telefax: +49 2129 5568-282 |
| e-mail: | info@bohle.de | |
| Contact person: | Klaus Nehren | Telephone: +49 2129 5568-276 |
| e-mail: | MSDS@bohle.de | |
| Internet: | www.bohle.com | |
| Responsible Department: | Chemie | |

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 02.09.2019

Product code: BO5209499

Page 2 of 9

| | |
|-----------|--|
| P233 | Keep container tightly closed. |
| P260 | Do not breathe vapour / aerosol. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P337+P313 | If eye irritation persists: Get medical advice/attention. |
| P312 | Call a POISON CENTER/doctor if you feel unwell. |
| P501 | Dispose of waste according to applicable legislation. |

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Hazardous components

| CAS No | Chemical name | | | Quantity |
|---------|---|--------------|----------|----------|
| | EC No | Index No | REACH No | |
| | GHS Classification | | | |
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | | | 90-100 % |
| | 200-661-7 | 603-117-00-0 | | |
| | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 | | | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Take off immediately all contaminated clothing.

After inhalation

Move to fresh air. Consult a physician after significant exposure. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. Call a physician immediately.

After contact with skin

Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

After contact with eyes

 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists, consult a specialist.

After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Give sodium sulfate as laxative (1 tablespoon in 1 glass of water) with plenty of activated coal.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 02.09.2019

Product code: BO5209499

Page 3 of 9

5.1. Extinguishing media**Suitable extinguishing media**water spray, alcohol-resistant foam, dry chemical, carbon dioxide (CO₂)**Unsuitable extinguishing media**

high volume water jet

5.2. Special hazards arising from the substance or mixture

In use may form flammable/explosive vapour-air mixture.

Fire may cause evolution of: Carbon monoxide, Carbon dioxide)

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

Additional information

Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation.

Keep away from heat and sources of ignition.

Avoid contact with skin and eyes. Do not breathe vapour.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Provide adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation as well as local exhaust at critical locations.

Provide room air exhaust at ground level.

Avoid formation of aerosol. Do not breathe vapour/aerosol.

Avoid contact with the skin and the eyes.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not smoke.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 02.09.2019

Product code: BO5209499

Page 4 of 9

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|---------|-------------|-----|-------------------|-----------|---------------|--------|
| 67-63-0 | Propan-2-ol | 400 | 999 | | TWA (8 h) | WEL |
| | | 500 | 1250 | | STEL (15 min) | WEL |

DNEL/DMEL values

| CAS No | Substance | Exposure route | Effect | Value |
|--------------------------|---|----------------|----------|-----------------------|
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | | | |
| Consumer DNEL, long-term | | oral | systemic | 26 mg/kg bw/day |
| Consumer DNEL, long-term | | dermal | systemic | 319 mg/kg bw/day |
| Worker DNEL, long-term | | dermal | systemic | 888 mg/kg bw/day |
| Consumer DNEL, long-term | | inhalation | systemic | 89 mg/m ³ |
| Worker DNEL, long-term | | inhalation | systemic | 500 mg/m ³ |

PNEC values

| CAS No | Substance | Value |
|--|---|------------|
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | |
| Freshwater | | 140,9 mg/l |
| Freshwater (intermittent releases) | | 140,9 mg/l |
| Marine water | | 140,9 mg/l |
| Freshwater sediment | | 552 mg/kg |
| Marine sediment | | 552 mg/kg |
| Micro-organisms in sewage treatment plants (STP) | | 2251 mg/l |
| Soil | | 28 mg/kg |

8.2. Exposure controls
Appropriate engineering controls

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

Protective and hygiene measures

Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Take off all contaminated clothing immediately. Keep away from food, drink and animal feedingstuffs. When using do not eat or drink. Do not smoke. Wash hands before breaks and at the end of workday.

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber) $\geq 0,5\text{mm}$, NBR (Nitrile rubber) $\geq 0,35\text{mm}$

Breakthrough time (maximum wearing time) ≥ 480 min.

Skin protection

impervious clothing

Respiratory protection

This product should not be used under conditions of poor ventilation unless a protective mask with an

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 02.09.2019

Product code: BO5209499

Page 5 of 9

appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|-----------------|-----------|
| Physical state: | liquid |
| Colour: | clear |
| Odour: | alcoholic |

| | |
|----------------------|--------------------|
| | Test method |
| pH-Value (at 20 °C): | neutral |

Changes in the physical state

| | |
|--|----------|
| Initial boiling point and boiling range: | 77-78 °C |
| Flash point: | 12 °C |

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

| | |
|-------------------------|-----------|
| Lower explosion limits: | 2 vol. % |
| Upper explosion limits: | 12 vol. % |
| Ignition temperature: | 425 °C |

Auto-ignition temperature

| | | |
|------------------|--------|--------------------|
| Vapour pressure: | 48 hPa | not auto-flammable |
|------------------|--------|--------------------|

| | |
|------------------------------------|------------------------|
| (at 20 °C) | |
| Density (at 20 °C): | 0,79 g/cm ³ |
| Water solubility: | soluble |
| Viscosity / dynamic: (at 20 °C) | 2,4 mPa·s |
| Vapour density: (at 20 °C) | 2 |
| Solvent content: | 100,00 % |

9.2. Other information**SECTION 10: Stability and reactivity****10.1. Reactivity**

None under normal processing.

10.2. Chemical stability

No decomposition if used as directed.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Keep away from heat and sources of ignition.

10.5. Incompatible materials

strong acids and oxidizing agents

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Pyrosil Primer

Revision date: 02.09.2019

Product code: BO5209499

Page 6 of 9

Acute toxicity

| CAS No | Chemical name | | | | |
|---------|---|---------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | | | | |
| | oral | LD50 mg/kg | 4570 | Rat | |
| | dermal | LD50 mg/kg | 13400 | Rabbit | |
| | inhalation (4 h) vapour | LC50 | 30 mg/l | Rat | |

Practical experience**Other observations**

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SECTION 12: Ecological information**12.1. Toxicity**

| CAS No | Chemical name | | | | | |
|---------|---|---------------|-----------|---|--------|--------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | | | | | |
| | Acute fish toxicity | LC50 mg/l | 9640 | 96 h Pimephales promelas (fathead minnow) | | |
| | Acute algae toxicity | ErC50 mg/l | >2000 | 72 h Desmodesmus subspicatus | | |

12.2. Persistence and degradability

Readily biodegradable, according to appropriate OECD test.

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

| CAS No | Chemical name | Log Pow |
|---------|---|---------|
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | -0,16 |

12.4. Mobility in soil

The product evaporates readily.

Further information

Water hazard class (WGK) 1: slightly water endangering

Do not let product enter drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

In accordance with local and national regulations.

Waste disposal number of waste from residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

Waste disposal number of used product

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 02.09.2019

Product code: BO5209499

Page 7 of 9

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

Waste disposal number of contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); plastic packaging

Contaminated packaging

Non-contaminated packages may be recycled.
Contaminated packages must be completely emptied and can be re-used following proper cleaning.
cleaning agent : Water

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 02.09.2019

Product code: BO5209499

Page 8 of 9



Special Provisions: -
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1219
14.2. UN proper shipping name: Isopropanol
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A180
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

none

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 95 Wt %. VOC-value (in g/L): 760
 Subcategory according to Directive 2004/42/EC: Preparatory and cleaning - Preparatory, VOC limit value: 850 g/l

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
 Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 02.09.2019

Product code: BO5209499

Page 9 of 9

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

| Classification | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 2; H225 | On basis of test data |
| Eye Irrit. 2; H319 | Calculation method |
| STOT SE 3; H336 | Calculation method |

Relevant H and EUH statements (number and full text)

| | |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)