

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 08.09.2022

Product code: BO5209499

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product identifier

Pyrosil Primer

Further trade names

BO 5209494, 50 ml, BO 5209490 SET, BO 5209491 SET
 BO 5209498, 250 ml
 BO 5209499, 1000 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against
Use of the substance/mixture

adhesives and/or sealants

1.3. Details of the supplier of the safety data sheet

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Dr. Martin Schade	Telephone: +49 2129 5568-300
e-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

1.4. Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture
Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
 Eye Irrit. 2; H319
 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements
Regulation (EC) No 1272/2008
Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:

Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 08.09.2022

Product code: BO5209499

Page 2 of 9

P233	Keep container tightly closed.
P260	Do not breathe vapour / Aerosol.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P337+P313	If eye irritation persists: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P501	Dispose of waste according to applicable legislation.

Labelling of packages where the contents do not exceed 125 ml
Signal word: Danger

Pictograms:

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			90-100 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	90-100 %
	inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg		

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

Take off immediately all contaminated clothing.

After inhalation

Move to fresh air. Consult a physician after significant exposure. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. Call a physician immediately.

After contact with skin

Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

After contact with eyes

 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists, consult a specialist.

After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Give sodium sulfate as laxative (1 tablespoon in 1 glass of water) with plenty of activated coal.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 08.09.2022

Product code: BO5209499

Page 3 of 9

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**water spray, alcohol-resistant foam, dry chemical, carbon dioxide (CO₂)**Unsuitable extinguishing media**

high volume water jet

5.2. Special hazards arising from the substance or mixture

In use may form flammable/explosive vapour-air mixture.

Fire may cause evolution of: Carbon monoxide, Carbon dioxide)

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

Additional information

Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Use personal protective equipment. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation.

Keep away from heat and sources of ignition.

Avoid contact with skin and eyes. Do not breathe vapour.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up**Other information**

Provide adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation as well as local exhaust at critical locations.

Provide room air exhaust at ground level.

Avoid formation of aerosol. Do not breathe vapour/aerosol.

Avoid contact with the skin and the eyes.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours are heavier than air and may spread along

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 08.09.2022

Product code: BO5209499

Page 4 of 9

floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not smoke.

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Take off all contaminated clothing immediately. Keep away from food, drink and animal feedingstuffs. When using do not eat or drink. Do not smoke. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-63-0	Isopropyl alcohol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³

PNEC values

CAS No	Substance	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 08.09.2022

Product code: BO5209499

Page 5 of 9

Appropriate engineering controls

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

Individual protection measures, such as personal protective equipment
Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber) $\geq 0,5\text{mm}$, NBR (Nitrile rubber) $\geq 0,35\text{mm}$

Breakthrough time: ≥ 480 min.

Skin protection

impervious clothing

Respiratory protection

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	clear
Odour:	alcoholic

Test method
Changes in the physical state

Boiling point or initial boiling point and boiling range: 77-78 °C

Flash point: 12 °C

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 2 vol. %

Upper explosion limits: 12 vol. %

Auto-ignition temperature: 425 °C

Self-ignition temperature

not auto-flammable

pH-Value (at 20 °C): neutral

Viscosity / dynamic: (at 20 °C) 2,4 mPa·s

Water solubility: soluble

Vapour pressure: (at 20 °C) 48 hPa

Density (at 20 °C): 0,79 g/cm³

Relative vapour density: (at 20 °C) 2

9.2. Other information

Solvent content: <100 %

Further Information

Pyrosil Primer

Revision date: 08.09.2022

Product code: BO5209499

Page 6 of 9

SECTION 10: Stability and reactivity
10.1. Reactivity

None under normal processing.

10.2. Chemical stability

No decomposition if used as directed.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Keep away from heat and sources of ignition.

10.5. Incompatible materials

strong acids and oxidizing agents

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	oral	LD50 mg/kg	4570	Rat		
	dermal	LD50 mg/kg	13400	Rabbit		
	inhalation (4 h) vapour	LC50	30 mg/l	Rat		

11.2. Information on other hazards
Other information

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SECTION 12: Ecological information
12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	96 h	Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 mg/l	72 h	Desmodesmus subspicatus		

12.2. Persistence and degradability

Readily biodegradable, according to appropriate OECD test.

12.3. Bioaccumulative potential

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 08.09.2022

Product code: BO5209499

Page 7 of 9

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	-0,16

12.4. Mobility in soil

The product evaporates readily.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Water hazard class 1: slightly water endangering

Do not let product enter drains.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

In accordance with local and national regulations.

List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); plastic packaging

Contaminated packaging

Non-contaminated packages may be recycled.

Contaminated packages must be completely emptied and can be re-used following proper cleaning.

cleaning agent : Water

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Special Provisions:	601
Limited quantity:	1 L

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 08.09.2022

Product code: BO5209499

Page 8 of 9

Excepted quantity: E2
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 601
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: -
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: Isopropanol
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A180
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pyrosil Primer

Revision date: 08.09.2022

Product code: BO5209499

Page 9 of 9

14.6. Special precautions for user

none

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC):

>95 weight-%. VOC value 760

Subcategory according to Directive

Preparatory and cleaning - Preparatory, VOC limit value: 850 g/l

2004/42/EC:

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information
Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)