

according to Regulation (EC) No 1907/2006

**Primer 150**

Revision date: 20.08.2018

Product code: BO6002006

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Primer 150

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

adhesives and/or sealants

**1.3. Details of the supplier of the safety data sheet**

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Klaus Nehren	Telephone: +49 2129 5568-276
e-mail:	MSDS@bohle.de	
Internet:	www.bohle-group.com	
Responsible Department:	Chemie	

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Reproductive toxicity: Repr. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

toluene

**Signal word:** Danger**Pictograms:****Hazard statements**

H225

Highly flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

according to Regulation (EC) No 1907/2006

## Primer 150

Revision date: 20.08.2018

Product code: BO6002006

Page 2 of 9

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

### Special labelling of certain mixtures

EUH208	Contains n-butyl methacrylate, methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate. May produce an allergic reaction.
--------	--

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**Chemical characterization**  
adhesives and/or sealants

#### Hazardous components

CAS No	Chemical name	Quantity
	EC No      Index No      REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
108-88-3	toluene	>25 %
	203-625-9      601-021-00-3	
	Flam. Liq. 2, Repr. 2, Asp. Tox. 1, STOT RE 2, Skin Irrit. 2, STOT SE 3; H225 H361d *** H304 H373 ** H315 H336	
71-36-3	butan-1-ol; n-butanol	<5 %
	200-751-6      603-004-00-6	
	Flam. Liq. 3, Acute Tox. 4, STOT SE 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3; H226 H302 H335 H315 H318 H336	
97-88-1	n-butyl methacrylate	<1 %
	202-615-1      607-033-00-5	
	Flam. Liq. 3, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2, Skin Sens. 1; H226 H319 H335 H315 H317	
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate	<1 %
	201-297-1      607-035-00-6	
	Flam. Liq. 2, STOT SE 3, Skin Irrit. 2, Skin Sens. 1; H225 H335 H315 H317	

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

according to Regulation (EC) No 1907/2006

**Primer 150**

Revision date: 20.08.2018

Product code: BO6002006

Page 3 of 9

**General information**

Take off immediately all contaminated clothing.

**After inhalation**

Move to fresh air. Consult a physician after significant exposure. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. Call a physician immediately.

**After contact with skin**

Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

**After contact with eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists, consult a specialist.

**After ingestion**

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Give sodium sulfate as laxative (1 tablespoon in 1 glass of water) with plenty of activated coal.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

water spray, alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media**

high volume water jet

**5.2. Special hazards arising from the substance or mixture**

In use may form flammable/explosive vapour-air mixture.  
Fire may cause evolution of: Carbon monoxide, Carbon dioxide )

**5.3. Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

**Additional information**

Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Keep people away from and upwind of spill/leak.  
Ensure adequate ventilation.  
Keep away from heat and sources of ignition.  
Avoid contact with skin and eyes. Do not breathe vapour.

**6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system.  
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.  
Local authorities should be advised if significant spillages cannot be contained.

**6.3. Methods and material for containment and cleaning up**

Provide adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Collect in closed and suitable containers for disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

according to Regulation (EC) No 1907/2006

## Primer 150

Revision date: 20.08.2018

Product code: BO6002006

Page 4 of 9

Personal protection equipment: see section 8  
 Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.  
 Provide room air exhaust at ground level.  
 Avoid formation of aerosol. Do not breathe vapour/aerosol.  
 Avoid contact with the skin and the eyes.

##### Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not smoke.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
71-36-3	Butan-1-ol	-	-		TWA (8 h)	WEL
		50	154		STEL (15 min)	WEL
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL

#### 8.2. Exposure controls

##### Appropriate engineering controls

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

##### Protective and hygiene measures

Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Take off all contaminated clothing immediately. Keep away from food, drink and animal feedingstuffs. When using do not eat or drink. Do not smoke. Wash hands before breaks and at the end of workday.

##### Eye/face protection

safety glasses with side-shields conforming to EN166

##### Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber)  $\geq 0,5\text{mm}$ , NBR (Nitrile rubber)  $\geq 0,35\text{mm}$

Breakthrough time (maximum wearing time)  $\geq 480$  min.

##### Skin protection

impervious clothing

according to Regulation (EC) No 1907/2006

**Primer 150**

Revision date: 20.08.2018

Product code: BO6002006

Page 5 of 9

**Respiratory protection**

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: liquid  
Colour: colourless  
Odour: characteristic

**Test method**

pH-Value: No data available

**Changes in the physical state**

Melting point: no data available  
Initial boiling point and boiling range: no data available  
Flash point: 8 °C

**Explosive properties**

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 1,2 vol. %  
Upper explosion limits: 7 vol. %

**Auto-ignition temperature**

not auto-flammable

Vapour pressure: 29 hPa  
(at 20 °C)  
Vapour pressure: 109 hPa  
(at 50 °C)

Density (at 20 °C): 0,92 g/cm<sup>3</sup>

Water solubility: practically insoluble  
(at 20 °C)

Viscosity / dynamic: no data available

**9.2. Other information****SECTION 10: Stability and reactivity****10.1. Reactivity**

None under normal processing.

**10.2. Chemical stability**

No decomposition if used as directed.

**10.3. Possibility of hazardous reactions**

Vapours may form explosive mixture with air.

**10.4. Conditions to avoid**

Keep away from heat and sources of ignition.  
Take action to prevent static discharges.

**10.5. Incompatible materials**

strong acids and oxidizing agents

**10.6. Hazardous decomposition products**

None known.

**SECTION 11: Toxicological information**

according to Regulation (EC) No 1907/2006

**Primer 150**

Revision date: 20.08.2018

Product code: BO6002006

Page 6 of 9

**11.1. Information on toxicological effects**
**Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-88-3	toluene				
	dermal	LD50 mg/kg	12200	Rabbit	GESTIS
	inhalative (4 h) vapour	LC50	49 mg/l	Rat	GESTIS
71-36-3	butan-1-ol; n-butanol				
	oral	ATE mg/kg	500		
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate				
	oral	LD50 mg/kg	7900	Rat	
	dermal	LD50 mg/kg	>5000	Rabbit	OECD 402
	inhalative (4 h) vapour	LC50	78 mg/l	Rat	

**Practical experience**
**Other observations**

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**SECTION 12: Ecological information**
**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50	13 mg/l	96 h	Carassius auratus	IUCLID
	Acute algae toxicity	ErC50 mg/l	12,5	72 h		GESTIS
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate					
	Acute fish toxicity	LC50	283 mg/l	96 h	Lepomis macrochirus (Bluegill)	
	Acute algae toxicity	ErC50	110 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50	69 mg/l	48 h	Daphnia magna (Big water flea)	

**12.2. Persistence and degradability**

Readily biodegradable, according to appropriate OECD test.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate			
	aerob	94%	14	
	Readily biodegradable (according to OECD criteria).			

according to Regulation (EC) No 1907/2006

## Primer 150

Revision date: 20.08.2018

Product code: BO6002006

Page 7 of 9

### 12.3. Bioaccumulative potential

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
80-62-6	methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate	1,38

### 12.4. Mobility in soil

The product evaporates readily.

#### Further information

Water hazard class (WGK) 2: water endangering

Do not let product enter drains.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

In accordance with local and national regulations.

#### Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

#### Waste disposal number of used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

#### Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

#### Contaminated packaging

Completely emptied packages can be recycled.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Primer 150

Revision date: 20.08.2018

Product code: BO6002006

Page 8 of 9

Hazard No: 33  
Tunnel restriction code: D/E

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (toluene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Special Provisions: 274 601 640D  
Limited quantity: 1 L  
Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (toluene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Special Provisions: 274  
Limited quantity: 1 L  
Excepted quantity: E2  
EmS: F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (toluene)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no



according to Regulation (EC) No 1907/2006

**Primer 150**

Revision date: 20.08.2018

Product code: BO6002006

Page 9 of 9

**14.6. Special precautions for user**

none

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not relevant

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 48: toluene

2004/42/EC (VOC): 86%

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH208	Contains n-butyl methacrylate, methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; methyl methacrylate. May produce an allergic reaction.

**Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*