

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX LV 740

Revision date: 12.11.2018

Product code: BOLV74010

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

UV Adhesive VERIFIX LV 740

Further trade names

BO LV74002, 20 g
BO LV74010, 100 g
BO LV74025, 250 g
BO LV7401K, 1000 g

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

adhesives

1.3. Details of the supplier of the safety data sheet

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Klaus Nehren	Telephone: +49 2129 5568-276
e-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Skin corrosion/irritation: Skin Corr. 1A
Serious eye damage/eye irritation: Eye Dam. 1
Respiratory or skin sensitisation: Skin Sens. 1
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Acute 1
Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause respiratory irritation.
Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate
acrylic acid, prop-2-enoic acid
2-hydroxyethyl methacrylate

Signal word: Danger**Pictograms:**

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX LV 740

Revision date: 12.11.2018

Product code: BOLV74010

Page 2 of 9

Hazard statements

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Methacrylate/Acrylate resin(s).

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	< 50%
	227-561-6	01-2119957862-25
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 2; H315 H319 H317 H335 H400 H411	
73324-00-2	Urethane acrylate	< 25%
	615-966-4	-
	Skin Irrit. 2, Eye Irrit. 2; H315 H319	
79-10-7	acrylic acid, prop-2-enoic acid	< 25%
	201-177-9	607-061-00-8
	01-2119452449-31	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Aquatic Acute 1 (M-Factor = 1); H226 H332 H312 H302 H314 H400	
868-77-9	2-hydroxyethyl methacrylate	< 25%
	212-782-2	607-124-00-X
	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

First aider: Pay attention to self-protection!
Get medical advice/attention if you feel unwell.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX LV 740

Revision date: 12.11.2018

Product code: BOLV74010

Page 3 of 9

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Irritation to respiratory tract

Skin contact : May cause an allergic skin reaction.

Eye contact : Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Extinguishing powder, Foam, Carbon dioxide (CO₂)

Unsuitable extinguishing media

High power water jet

5.2. Special hazards arising from the substance or mixture

Burning produces irritant fumes. Carbon monoxide, Carbon dioxide, Hydrocarbons, Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment (refer to section 8).

Provide adequate ventilation.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Avoid contact with skin and eyes.

Do not eat, drink or smoke when using this product.

Ensure adequate ventilation.

UV Adhesive VERIFIX LV 740

Revision date: 12.11.2018

Product code: BOLV74010

Page 4 of 9

Advice on protection against fire and explosion

No special technical protective measures required.

Further information on handling

Avoid: UV-radiation/sunlight

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up.

Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
8.2. Exposure controls
Protective and hygiene measures

Wash hands before breaks and after work. When using do not eat, drink or smoke.

Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Recommended material: NBR (Nitrile rubber), VITON

Unsuitable material: Natural fibres (e.g. cotton)

Skin protection

Wear suitable protective clothing.

Respiratory protection

Usually no personal respirative protection necessary. When using do not eat, drink or smoke.

In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (DIN EN 136/140)

Respirator with filter for organic vapour. Recommended Filter type: A (P2)

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	characteristic

Changes in the physical state

Viscosity / dynamic: (at 23 °C)	80 mPa·s
------------------------------------	----------

Solvent content:	0%
------------------	----

SECTION 10: Stability and reactivity
10.1. Reactivity

Light / UV-radiation/sunlight

Oxidising agent, strong

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX LV 740

Revision date: 12.11.2018

Product code: BOLV74010

Page 5 of 9

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep cool. Protect from sunlight. Heat, flames and sparks.
In case of light influence: Polymerisation

10.5. Incompatible materials

Reducing agent, strong. Oxidising agent, strong
strong acids and strong bases

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.
Thermal decomposition can lead to the escape of irritating gases and vapours. Carbon monoxide (CO),
Carbon dioxide (CO₂), Hydrocarbons

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate				
	oral	LD50 mg/kg	4890	Rat	
	dermal	LD50 mg/kg	>5000	Rabbit	
79-10-7	acrylic acid, prop-2-enoic acid				
	oral	LD50 mg/kg	500	Rat	
	dermal	LD50 mg/kg	1100	Rat	
	inhalative (4 h) vapour	LC50	11 mg/l	Rat	
	inhalative aerosol	ATE	1,5 mg/l		
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50 mg/kg	5050	Rat	
	dermal	LD50 mg/kg	>5000	Rabbit	

Irritation and corrosivity

Causes severe burns.
Irritating to respiratory system.

Sensitising effects

May cause sensitisation by skin contact. (2-hydroxyethyl methacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX LV 740

Revision date: 12.11.2018

Product code: BOLV74010

Page 6 of 9

STOT-single exposure

Based on available data, the classification criteria are not met.
 Inhalative specific target organ toxicity (single exposure)
 Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate: Category 3
 acrylic acid, prop-2-enoic acid: Category 3

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information
12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate					
	Acute fish toxicity	LC50 mg/l	0,704	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50 mg/l	1,98	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	1,1 mg/l	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC mg/l	0,405	3 d	Pseudokirchneriella subcapitata	
	Crustacea toxicity	NOEC mg/l	0,092	21 d	Daphnia magna (Big water flea)	
79-10-7	acrylic acid, prop-2-enoic acid					
	Acute fish toxicity	LC50	27 mg/l	96 h	Onchorhynchus mykiss	
	Acute algae toxicity	ErC50 mg/l	0,13	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50	95 mg/l	48 h	Daphnia magna	
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas	

12.2. Persistence and degradability

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate				
	Decomposition with: Water	57%	28		

12.3. Bioaccumulative potential
Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
79-10-7	acrylic acid, prop-2-enoic acid	0,35
868-77-9	2-hydroxyethyl methacrylate	0,47

Further information

No data is available on the product itself.

SECTION 13: Disposal considerations

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX LV 740

Revision date: 12.11.2018

Product code: BOLV74010

Page 7 of 9

13.1. Waste treatment methods

Advice on disposal

Consult the appropriate local waste disposal expert about waste disposal.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

- 14.1. UN number:** UN 1760
- 14.2. UN proper shipping name:** CORROSIVE LIQUID, N.O.S. (acrylic acid, prop-2-enoic acid)
- 14.3. Transport hazard class(es):** 8
- 14.4. Packing group:** III

Hazard label:



- Classification code: C9
- Special Provisions: 274
- Limited quantity: 5 L
- Excepted quantity: E1
- Transport category: 3
- Hazard No: 80
- Tunnel restriction code: E

Inland waterways transport (ADN)

- 14.1. UN number:** UN 1760
 - 14.2. UN proper shipping name:** CORROSIVE LIQUID, N.O.S. (acrylic acid, prop-2-enoic acid)
 - 14.3. Transport hazard class(es):** 8
 - 14.4. Packing group:** III
- Hazard label: 8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX LV 740

Revision date: 12.11.2018

Product code: BOLV74010

Page 8 of 9



Classification code: C9
 Special Provisions: 274
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1760
14.2. UN proper shipping name: CORROSIVE LIQUID, N.O.S. (Acrylic Acid)
 Marine pollutant (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate, Acrylic Acid)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
 Hazard label: 8



Special Provisions: 223, 274
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1760
14.2. UN proper shipping name: CORROSIVE LIQUID, N.O.S. (Acrylic Acid)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
 Hazard label: 8



Special Provisions: A3 A803
 Limited quantity Passenger: 1 L
 Passenger LQ: Y841
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 852
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 856
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes


SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX LV 740

Revision date: 12.11.2018

Product code: BOLV74010

Page 9 of 9

EU regulatory information

2004/42/EC (VOC): 0 %
0 g/l

Information according to 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)