

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX MV 760

Revision date: 05.03.2020

Product code: BOMV76010

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

UV Adhesive VERIFIX MV 760

Further trade names

BO MV76002, 20 g
BO MV76010, 100 g
BO MV76025, 250 g / BO MV76025S, Spacer, 250 g
BO MV7601K, 1000 g / BO MV7601KS, Spacer, 1000 g

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

adhesives

1.3. Details of the supplier of the safety data sheet

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	D-42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Klaus Nehren	Telephone: +49 2129 5568-276
e-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

1.4. Emergency telephone number: Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
Skin corrosion/irritation: Skin Corr. 1A
Serious eye damage/eye irritation: Eye Dam. 1
Respiratory or skin sensitisation: Skin Sens. 1
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Acute 1
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Causes severe skin burns and eye damage.
Causes serious eye damage.
May cause an allergic skin reaction.
May cause respiratory irritation.
Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate
Acrylic acid
2-hydroxyethyl methacrylate

Signal word: Danger

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX MV 760

Revision date: 05.03.2020

Product code: BOMV76010

Page 2 of 10

Pictograms:

Hazard statements

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Methacrylate/Acrylate resin(s).

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	< 50%		
	227-561-6		01-2119957862-25	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 2; H315 H319 H317 H335 H400 H411			
73324-00-2	Urethane acrylate	< 50%		
	615-966-4		-	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
79-10-7	Acrylic acid	< 25%		
	201-177-9	607-061-00-8	01-2119452449-31	
	Flam. Liq. 3, Met. Corr. 1, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Eye Irrit. 2, STOT SE 3, Aquatic Acute 1 (M-Factor = 1); H226 H290 H332 H312 H302 H314 H319 H335 H400			
868-77-9	2-hydroxyethyl methacrylate	< 10%		
	212-782-2	607-124-00-X	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX MV 760

Revision date: 05.03.2020

Product code: BOMV76010

Page 3 of 10

General information

First aider: Pay attention to self-protection!
Get medical advice/attention if you feel unwell.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: Irritation to respiratory tract
Skin contact : May cause an allergic skin reaction.
Eye contact : Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Extinguishing powder, Foam, Carbon dioxide (CO₂)

Unsuitable extinguishing media

High power water jet

5.2. Special hazards arising from the substance or mixture

Burning produces irritant fumes. Carbon monoxide, Carbon dioxide, Hydrocarbons, Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment (refer to section 8).
Provide adequate ventilation.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.
Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

6.4. Reference to other sections

Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX MV 760

Revision date: 05.03.2020

Product code: BOMV76010

Page 4 of 10

Advice on safe handling

Avoid contact with skin and eyes.
Do not eat, drink or smoke when using this product.
Ensure adequate ventilation.

Advice on protection against fire and explosion

No special technical protective measures required.

Further information on handling

Avoid: UV-radiation/sunlight

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place.
Keep container tightly closed. Keep locked up.
Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
79-10-7	Acrylic acid	10	29		TWA (8 h)	EU
		20	59		STEL (1 min)	EU

8.2. Exposure controls**Protective and hygiene measures**

Wash hands before breaks and after work. When using do not eat, drink or smoke.
Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.
Recommended material: NBR (Nitrile rubber), VITON
Unsuitable material: Natural fibres (e.g. cotton)

Skin protection

Wear suitable protective clothing.

Respiratory protection

Usually no personal respirative protection necessary. When using do not eat, drink or smoke.
In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (DIN EN 136/140)
Respirator with filter for organic vapour. Recommended Filter type: A (P2)

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid
Colour: colourless
Odour: characteristic

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX MV 760

Revision date: 05.03.2020

Product code: BOMV76010

Page 5 of 10

Changes in the physical stateViscosity / dynamic: 1500 mPa·s
(at 23 °C)

Solvent content: 0%

9.2. Other information

not auto-flammable

SECTION 10: Stability and reactivity**10.1. Reactivity**Light / UV-radiation/sunlight
Oxidising agent, strong**10.2. Chemical stability**

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoidKeep cool. Protect from sunlight. Heat, flames and sparks.
In case of light influence: Polymerisation**10.5. Incompatible materials**Reducing agent, strong. Oxidising agent, strong
strong acids and strong bases**10.6. Hazardous decomposition products**No decomposition if stored and applied as directed.
Thermal decomposition can lead to the escape of irritating gases and vapours. Carbon monoxide (CO),
Carbon dioxide (CO₂), Hydrocarbons**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX MV 760

Revision date: 05.03.2020

Product code: BOMV76010

Page 6 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate				
	oral	LD50 mg/kg 4890	Rat		
	dermal	LD50 mg/kg >5000	Rabbit		
79-10-7	Acrylic acid				
	oral	LD50 mg/kg 33,5	Rat		
	dermal	LD50 mg/kg 640	Rabbit		
	inhalation (4 h) vapour	LC50 11 mg/l	Rat		
	inhalation aerosol	ATE 1,5 mg/l			
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50 mg/kg 5050	Rat		
	dermal	LD50 mg/kg >5000	Rabbit		

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate; 2-hydroxyethyl methacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate; Acrylic acid)

Inhalative specific target organ toxicity (single exposure)

 Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate: Category 3
 acrylic acid; prop-2-enoic acid: Category 3

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information
12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX MV 760

Revision date: 05.03.2020

Product code: BOMV76010

Page 7 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate					
	Acute fish toxicity	LC50 mg/l	0,704	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50 mg/l	1,98	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	1,1 mg/l	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC mg/l	0,405	3 d	Pseudokirchneriella subcapitata	
	Crustacea toxicity	NOEC mg/l	0,092	21 d	Daphnia magna (Big water flea)	
79-10-7	Acrylic acid					
	Acute fish toxicity	LC50	27 mg/l	96 h	Onchorhynchus mykiss	
	Acute algae toxicity	ErC50 mg/l	0,13	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50	95 mg/l	48 h	Daphnia magna	
	Crustacea toxicity	NOEC	3,8 mg/l	21 d	Daphnia magna (Big water flea)	
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas	

12.2. Persistence and degradability

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate				
	Decomposition with: Water	57%	28		

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
79-10-7	Acrylic acid	0,35
868-77-9	2-hydroxyethyl methacrylate	0,47

Further information

No data is available on the product itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Consult the appropriate local waste disposal expert about waste disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX MV 760

Revision date: 05.03.2020

Product code: BOMV76010

Page 8 of 10

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste


Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)


14.1. UN number: UN 1760
14.2. UN proper shipping name: CORROSIVE LIQUID, N.O.S. (acrylic acid; prop-2-enoic acid)
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Classification code: C9
 Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 80
 Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 1760
14.2. UN proper shipping name: CORROSIVE LIQUID, N.O.S. (acrylic acid; prop-2-enoic acid)
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8



Classification code: C9
 Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1760
14.2. UN proper shipping name: CORROSIVE LIQUID, N.O.S. (Acrylic Acid)
 Marine pollutant (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate, Acrylic Acid)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX MV 760

Revision date: 05.03.2020

Product code: BOMV76010

Page 9 of 10

14.3. Transport hazard class(es): 8

14.4. Packing group: II

Hazard label: 8



Special Provisions: 274

Limited quantity: 1 L

Excepted quantity: E2

EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1760

14.2. UN proper shipping name: CORROSIVE LIQUID, N.O.S. (Acrylic Acid)

14.3. Transport hazard class(es): 8

14.4. Packing group: II

Hazard label: 8



Special Provisions: A3 A803

Limited quantity Passenger: 0.5 L

Passenger LQ: Y840

Excepted quantity: E2

IATA-packing instructions - Passenger: 851

IATA-max. quantity - Passenger: 1 L

IATA-packing instructions - Cargo: 855

IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 0 %

0 g/l

Information according to 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 3 - strongly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

according to Regulation (EC) No 1907/2006

UV Adhesive VERIFIX MV 760

Revision date: 05.03.2020

Product code: BOMV76010

Page 10 of 10

SECTION 16: Other information**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)